

Appl. No. 10/700,614
Atty. Docket No. 9422L
Amendment dated July 19, 2005
Response to Advisory Action of 07/08/2005
Customer No. 27752

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) An applicator for applying a sheet material to a substrate, said applicator comprising at least two burnishes, each said burnish comprising an outwardly facing first surface for burnishing said sheet material and, said two burnishes being disposed so that said first surfaces subtend an included angle of at least 180° , at least one said burnish being flat.
2. (Previously presented) An applicator according to claim 1, wherein each said burnish is flat.
3. (Original) An applicator according to claim 2, wherein said burnishes may be extrapolated to intersect at a vertex, each said burnish being offset from said vertex.
4. (Original) An applicator according to claim 3, wherein said first surfaces of said burnish subtend an included angle of at least 270° .
5. (Original) An applicator according to claim 2, wherein said burnishes comprise mutually different materials.
6. (Original) An applicator according to claim 1, wherein said burnishes subtend an included angle of less than 180° opposite said first surfaces, said applicator further comprising a holder, said holder being disposed within said included angle of less than 180° .

Appl. No. 10/700,614
Atty. Docket No. 9422L
Amendment dated July 19, 2005
Response to Advisory Action of 07/08/2005
Customer No. 27752

7. (Original) An applicator according to claim 6, wherein said burnishes and said holder are elongate, and said aperture defines an elongate slit, said slit being disposed above one said burnish when said one burnish is disposed against a vertical substrate.
8. (Original) An applicator according to claim 1, wherein said applicator is disposable against a flat substrate, said applicator further comprising a control bar for attachment to a sheet material, said control bar being movable between an deployed position and a retractable position, whereby said control bar is juxtaposable with a corner formed by said substrate when said control bar is extended to said deployed position.
9. (Original) An applicator according to claim 1, wherein said at least one burnish comprises a compliant material.
10. (Original) An applicator according to claim 9, wherein at least one said burnish comprises felt.
11. (Canceled)
12. (Canceled)
13. (Currently amended) An applicator for applying a sheet material to a substrate, said applicator comprising at least two non-rotatable burnishes, at least one said burnish having an arcuate and outwardly facing first surface for burnishing said sheet material onto the substrate, said other burnish also having an outwardly facing first surface, whereby both of said first surfaces can burnish said sheet material while said applicator is in use, said first surfaces of said burnishes being disposed in convex noncoplanar relationship relative each other, wherein said applicator comprises two burnishes, at least one of said burnishes having a first surface which is convexly shaped, each said burnish having a major axis, said applicator having a hinge generally parallel to said major axis, at least one said burnish being articulable relative to the other said burnish about said hinge.

Appl. No. 10/700,614
Atty. Docket No. 9422L
Amendment dated July 19, 2005
Response to Advisory Action of 07/08/2005
Customer No. 27752

14. (Previously presented) An applicator according to claim 13, wherein said first surfaces of said two burnishes comprise mutually different materials.

15-19 (Canceled)